

Probe PI-01LF for Smart Fieldmeter® and Smart Fieldmeter® Digital meters

Isotropic Broadband Electric Field Probe PI-01LF: 10 KHz-3 GHz, 0.3-600 V/m

Broadband probe PI-01LF, meets the requirements of various EMC and RF safety standards. It allows measurements of RF fields produced by most of the broadcast, telecommunication and industrial sources. This probe eliminates the need for two probes to cover the required frequency range 10 KHz- 3 GHz, thus making measurements simpler and faster.



Main Parameters*

- Diode based: 3-Axial isotropic sensor.
- High sensitivity: 0.3 V/m ($F > 200$ KHz)
- Sensitivity limit: 3 V/m ($F \sim 10$ KHz)
- Linearity: ± 0.5 dB (1-600 V/m)
- Dynamic range: > 66 dB (single range).
- Frequency response (without correction factors):
 - 10 MHz-1 GHz (± 1 dB),
 - 1-3 GHz (+1, - 3 dB).
 - 100 KHz - 10 MHz (± 2 dB)
 - 10-100 KHz (linear slope from 100 KHz).
- Frequency response (with correction factors):
 - 10 KHz-1 GHz (± 1 dB),
 - 1-3 GHz (± 1.5 dB).
- Rotational isotropicity: < 1 dB (typical 0.5 dB).
- Calibration accuracy (at specified freq.) < 1 dB.
- Temperature: 5-40 °C,
- Humidity: RH 10-90%, non-condensing.
- Temperature error: < 0.05 dB/°C (field > 2 V/m).
- UK NPL or NIST traceable calibration.
- Small size: LxD: 9.0x2.25 inch, 230x58 mm.
- Weight: 0.2 lb, 100 g.
- Operates with both RFP-04 and RFP-05 meters.
- **Designed and made in the USA.**

EMC Test Design, LLC®
P.O. Box 600532,
Newton, MA 02460, USA
www.emctd.com,
exid@emctd.com,
508-292-1833.



** Specification may be changed to reflect the design progress.*

** All system parameters are given for RFP-05 meter.*