Application Guide For Smart Fieldmeter®, Smart Fieldmeter® Digital And Omnifield Antenna®

And Omnifield Antenna®				
	Smart Fieldmeter® Digital. Models RFP-05, RFP-05M	Smart Fieldmeter® Model RFP-04	Omnifield Antenna® Models OFA-S, OFA-SE	
Look				
Description	Isotropic 3-axis probe with advanced design meter measuring the RF field strength. Multi-probe unit with built-in recording capabilities.	Isotropic 3-axis probe with meter measuring the RF field strength. Single probe unit with simplest user interface.	Unique Isotropic 3- axis antenna, producing the RF signal proportional to the RF field strength.	
Applications	- EMC testing for CE, MIL and industrial EMC qualification RF field strength monitoring for health, safety and industrial or military environmental control RF compliance testing of active transmitters: TV, Cell, Radio and other industrial sources RF monitoring of MW ovens and other industrial power RF applications Scientific and medical research of biological effects of electromagnetic radiation and electrosmog.	 EMC testing for CE, MIL and industrial EMC qualification. RF field strength monitoring for health, safety and industrial or military environmental control. RF compliance testing of active transmitters: TV, Cell, Radio and other industrial sources. RF monitoring of MW ovens and other industrial power RF applications. Scientific and medical research of biological effects ofelectromagnetic radiation and electrosmog. 	- Selective measurement of RF signals when spectral analysis of the field is important RF field strength monitoring for health, RF safety and industrial or military environmental control Scientific and medical research of biological effects of electromagnetic radiation and electrosmog.	

EMC Test Desig	The versatile EMC test lab in your hand. Meter supports up to four different probes and stores the results on the removable memory card. Have auto ranging, auto zeroing, and alarm and performs time and spatial	Simple professional field strength meter for field and lab use. Measures the RF field strength with one dedicated probe. Uses decoupled wired or fiber optic link to a PC. Peak, Pulse and Average	The unique isotropic small size RF antenna operating with any spectrum analyzer of your choice. Output RF signal is proportional to the RF field amplitude.
	averaging. Fully adjustable data logging with time and GPS position stamp. Bidirectional link to a PC with wired optically decoupled or fiber optic connection. Flexible and upgradeable architecture.	modes. Semiautomatic auto zeroing. Classic time proven design.	Measure the field strength and the frequency of the RF transmitters.
Frequency Response	Specified by the probe type. Supports all electric field probes (10 KHz-18 GHz), magnetic field probe (500 KHz-50 MHz) and electric pulsed field probe (100 MHz-18 GHz). Deviations are specified by frequency correction factors.	Specified by the probe type. Supports one electric field probe (10 KHz -18 GHz). Deviations are specified by frequency correction factors.	Specified by the antenna factors in the frequency range 30 MHz-3 GHz.
Field Range	0.2 V/m-800 V/m	0.2 V/m-800 V/m	10 mV/m-200 V/m (OFA-S). 1 mV/m-20 V/m (OFA-SE)
Additional Equipment	Not required for normal operation. Field Gauge® is included. ODLK PC link kit and FOLK-01 fiber optic link kit (for RFP-05), IM Insulated Modem and FOLK-02 (for RFP-05M), and GPS-R receivers are provided as an option.	Not required for normal operation. Field Gauge® is included. PCLK-01 PC link kit, FOLK-01 fiber optic link kit and data loggers for data storage are provided as an option.	SA USB Spectrum Analyzer in SFA-S kit. Any standard spectrum analyzer. Portable one is the best choice for field applications.
Calibration	United Kingdom NPL traceable	United Kingdom NPL traceable	United Kingdom NPL traceable
Warranty	1 Year, parts and labor.	1 Year, parts and labor.	1 Year, parts and labor.
Made by	EMC Test Design, LLC USA	EMC Test Design, LLC USA	EMC Test Design, LLC, USA